Application No.: 10/098,681 Docket No.: X2278.0037/P037

## AMENDMENTS TO THE SPECIFICATION

Paragraph at page 3, lines 16-27:

In Fig. 1, which is a plan view illustrating a prior art LCD apparatus, a gate bus line  $GL_i$  (i=1, 2, ..., m) and a signal bus lines  $SL_j$  (j=1, 2, ..., n) are provided on a transparent substrate [[17]] 11, and a pixel  $P_{ij}$  is provided at an intersection between the gate bus line  $GL_i$  and the signal bus line  $SL_j$ . Also, the pixel  $P_{ij}$  is constructed by a thin film transistor (TFT) Q, a liquid crystal cell LC and a storage capacitor SC. In this case, the liquid crystal cell LC is connected to a common electrode line [[ $CE_j$ ]]  $CE_i$  arranged in parallel with the gate bus line  $GL_i$ . Also, the storage capacitor SC is connected to an adjacent gate line in a gate storage type or a storage line (not shown) in a storage capacitor type, thereby substantially increasing the capacitance of the liquid crystal cell LC.

Paragraph at page 4, lines 5-12:

In the LCD apparatus of [[Fig.]] Figs. 1 and 2, in order to easily specify a defective location, an address mark is provided for the gate bus line GLi and the common electrode line  $CE_i$  (i=1, 2, ..., m) as illustrated in Fig. 3 (see Fig. 3 of JP-A-2000-147549). For example, a scan address mark "617" is provided for the gate bus line  $GL_{617}$  and the common electrode line  $CE_{617}$ , and a scan address mark "618" is provided for the gate bus line  $GL_{618}$  and the common electrode line  $CE_{618}$ .

Application No.: 10/098,681 Docket No.: X2278.0037/P037

Paragraph at page 4, line 30 to page 5, line 1:

In Fig. 7, which illustrates a first embodiment of the LCD apparatus according to the present invention, an address  $\underline{mark}$  marks provided for the gate bus line  $GL_i$  and the common electrode line  $CE_i(i=1, 2, ..., m)$  is connected to the common electrode line  $CE_i(i=1, 2, ..., m)$ . For example, a scan address mark "617" is connected to the common electrode line  $CE_{617}$ , and a scan address mark "618" is connected to the common electrode line  $CE_{618}$ .